

# **TECHNICAL DATA SHEET**

## APW PLOSTICHT 524

APW Phostight<sub>524</sub> is used in cleaning parts and phosphatizing them before they are painted. Anyone that paints is a potential phosphatizer customer. APW Phostight<sub>524</sub> works through a machine conveyer tunnel or in an automatic parts washer. APW Phostight<sub>524</sub> contains our exclusive blend of surfactants to prolong the working life in an automatic parts washer. It is used as a wash application, and also an iron phosphate coating. It works to assure paint adhesion as well as corrosion resistance. A pressure washer or parts washer can be sold just for phosphatizing. APW Phostight<sub>524</sub> helps passivate the surface. Citrax<sub>521</sub> can be added for additional cleaning and degreasing. Citrax<sub>521</sub> is neutral and won't interfere with phosphatizing. D-Foam<sub>552</sub> may be necessary to manage foam as soil loading increases over time in parts washer tank.

#### **Product Highlights**

- Working as a cleaner and phosphatizer at the same time.
- Economical per gallon cost.
- Designed specifically for automatic parts washers and pressure washers.
- Designed for hot or cold washing. Exclusive water softening package to aid in hard water
- conditions. Works well in hard or soft water.
- Newest corrosion inhibitors to protect equipment and prevent flash rusting.
- Non-Hazardous. Non-Corrosive.
- Does not carry ingredients that attack the earth's ozone, or contribute to smog.

### **Physical Description**

- 19% Active Ingredients
- $\Rightarrow$  Flash point = > 200° F
- pH 5% Solution = 3.2
- $\diamond$  Specific Gravity = 1.08
- ♦ VOC = 22 g/L
- Does ship UPS
- $\diamond$  Shelf Life = 2 years
- Freeze / thaw stable
- ♦ Appearance = Clear liquid

#### **Application Directions:**

- Heavy: 1-part APW Phostight<sub>524</sub> to 30-parts water.
- Medium: 1-part APW Phostight<sub>524</sub> to
  60-parts water.
- Light: 1-part APW Phostight<sub>524</sub> to 100-parts water.

Works best if used in temperatures of 120-180 degrees Fahrenheit. For more difficult soil increase the amount of APW Phostight<sub>524</sub> accordingly.

Available inKit  $\Rightarrow$  5 Gal Pail  $\Rightarrow$  55 Gal Drum  $\Rightarrow$  275 Gal Tote

HYDRUS DETERGENTS 2621 7th Ave S Estherville, IA 51334 (712) 765 1060 www.hydrusdetergents.com

PARTS WASHER