## **TECHNICAL DATA SHEET**



# APW PRO WHITE 5611

APW Pro White<sub>531L</sub> is an alkaline, fully biodegradable parts washer/all purpose detergent. APW Pro White<sub>531L</sub> is made specifically for use in automatic parts washers and soak tank applications. APW Pro White<sub>531L</sub> contains a heavy duty de-foamer package to eliminate foaming and contains no chelating agents. Works well in cleaning steel, brass, aluminum iron, plastics and painted surfaces. APW Pro White<sub>531L</sub> works extremely well as an industrial floor cleaner through floor scrubbers. APW Pro White<sub>531L</sub> contains a multi-metal rust and corrosion inhibitor package. This synergistic blend of ingredients protect virtually all metals except galvanized. An invisible anti-corrosion shield gives months of indoor corrosion protections when used in a non-rinsing automatic parts washer.

## **Product Highlights**

- Contains exclusive surfactant system for excellent cleaning results.
- ♦ Economical per gallon cost.
- De-foaming agents and rinse aids prolong cleaning life and make additional expensive de-foamers unnecessary in most applications.
- Designed for automatic parts washers, soak tanks/floor scrubbers.
- Designed for hot or cold washing. Exclusive water softening package to aid in hard water conditions. Works well in hard or soft water.
- Contains exclusive anti corrosion package. Prevents flash rusting and protects equipment from hard water build up.
- Non-Hazardous. Non-Corrosive. Fully Biodegradable. No chlorinated solvents.
- Does not carry ingredients that attack the earth's ozone, or contribute to smog.

## **Physical Description**

- ♦ 17% Active Ingredients
- ightharpoonup Flash point = > 200° F
- ♦ pH 5% Solution = 12
- ♦ Specific Gravity = 1.15
- ♦ VOC = <1 g/L</p>
- Does ship UPS
- ♦ Shelf Life = 2 years
- ♦ Freeze / thaw stable
- ♦ Appearance = Tan liquid

#### **Application Directions:**

- ♦ HEAVY= 1-part to 15 parts water
- ♦ MEDIUM= 1-part to 30 parts water.
- ♦ LIGHT= 1-part to 50 parts water.

It is best to use in 140-180 degrees Fahrenheit. Depending on the severity, adjust the detergent accordingly. For floor scrubbing use 1 part APW Pro White<sub>531L</sub> to 60-100 parts water.

### Available in

Kit ♦ 5 Gal Pail ♦ 55 Gal Drum ♦ 275 Gal Tote

#### **HYDRUS DETERGENTS**

2621 7th Ave S Estherville, IA 51334 (712) 765 1060 www.hydrusdetergents.com